

H-28

2D CMOS Imager

Built with a durable and intelligent design, the H-28 is ideal for today's mobile workforce. Implementing a variety of applications that make it an optimal tool to be used in areas such as: field sales, inventory management, and logistics.



Highlights

- Rugged mobile computer with a fully integrated, high speed 2D imager barcode scanner
- Android 6.01 for familiar and convenient navigation
- Qualcomm SD 617 A53 Octa-core platform: 1.5 GHz Quad-core and 1.2 GHz Quad-core
- 5" brilliant color touchscreen display with Gorilla® Glass, anti-reflective coating and signature capture
- Communications: Bluetooth 4.1 LE, WLAN, Wi-Fi, NFC, USB
- Rear facing 16 MP auto-focus digital camera, LED flash, front facing 5 MP
- IP67 rating against dust and moisture, survives multiple 1.8 m drops to concrete, MIL-STD 810G with bumper
- Memory: 16GB EMMC, 2GB LPDDR3 RAM and MicroSD
- Compact form factor: 77 x 158 x 16.9 mm (W x H x D) and 308 grams
- User/field-replaceable battery packs (no special tool needed), supports hot-swap mode, standard and extended battery packs available
- Supports Qualcomm Quick-Charge feature, which can charge the standard battery pack from 0 to 75% within 45 min
- Soti and Signify certified
- Two year warranty and OptiCare comprehensive warranty option

H-28

Product Specifications

Operation

CPU: Qualcomm Snapdragon 617 A53 Octa-core
O/S: Android 6.0.1

Memory

EMMC: 16GB
RAM: LPDDR3 2GB
Expansion: MicroSD

Display

Type: FHD, capacitive touch panel, color screen, Gorilla Glass.
Size: 5"
Brightness: 500 cd/m2 (nits)

Operating indicators

Visual: 3 LEDs
Non-visual: Vibrate, dual speakers (max 105dB)

Operating keys

Entry options: 1 power key, 2 volume keys, 2 (programmable) scan keys, 2 function keys, 3 OS keys

Communication

Bluetooth: 4.1 LE
W-LAN: Wi-Fi, IEEE 802.11 a/b/g/n/ac/r
WAN: WCDMA, GSM, TDD LTE, FDD LTE
NFC: ISO14443-4 (type A & B), SE SIM, ISO15693, Mifare, Felica (ISO/IEC18092)
GPS: GPS/GLONASS (WWAN only)

Sensors

Accelerometer, Light sensor, gyroscope, E-compass, Proximity

Power

Main battery: Lithium-Ion 3.7V 2960mAh (Standard), Lithium-Ion 3.7V 5920mAh (optional)
Backup battery: Rechargeable RTC battery, battery swap
Operating time (WWAN on, LCD on): Ca. 9 hours (standard), Ca. 18 hours (extended)
Charging technology: Qualcomm Quickcharge 2.0(USB only)

Camera

Rear facing camera: 16 MP, auto-focus, LED flash
Front facing camera: 5 MP

2D Imager optics

Light source: Aiming green LED, warm white illumination LED
Scan method: CMOS area sensor, 640 x 480 pixels, greyscale 10-bits
Scan rate: Up to 100 fps
Reading pitch angle: -65 to 0°, 0 to +65°
Reading skew angle: -65 to 0°, 0 to +65°
Reading tilt angle: 360°
Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
Min. resolution at pcs 0.9: 0.1 mm / 4 mil
Min. pcs value: 0.2
Field of view: Horizontal 38°, Vertical 28.9°
Depth of field at code 39:
52 - 126 mm (0.127 mm) / 2.05 - 4.96 in (5 mil),
46 - 246 mm (0.254 mm) / 1.81 - 9.68 in (10 mil),
60 - 466 mm (0.508 mm) / 2.36 - 18.35 in (20 mil)
Depth of field at QR code:
64 - 106 mm (0.169mm) / 2.52 - 4.17 in (6.7 mil),
30 - 234 mm (0.381mm) / 1.18 - 9.21 in (15 mil)

Supported symbologies

Barcode (1D): JAN/UPC/EAN incl. add on, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 Databar (RSS), IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN-IS-MN, Matrix 2of5, MSI/Plessey, S-Code, Telepen, Tri-Optic, UK/Plessey
Postal code: Chinese Post, Intelligent Mail Barcode, Korean Postal Authority code, POSTNET
2D code: Aztec Code, Aztec Runes, Chinese Sensible code, Codablock F, Composite codes, Data matrix

(ECC200), Passport MRZ (OCR-B), maxi Code (mode 2-5), MicroPDF417, MicroQR Code, PDF417, QR Code

Durability

Temperature in operation: -20 to 50 °C / -4 to 122 °F
Temperature in storage: -30 to 60 °C / -22 to 140 °F (without battery)
Humidity in operation: 10% to 90% (non-condensing)
Humidity in storage: 10% to 90% (non-condensing)
Drop test: 1.5m / 5 ft drop onto concrete surface, MIL-STD 810G. 1.8m / 6 ft drop onto concrete surface, MIL-STD 810G with protective bumper
Protection rate: IP67

Physical

Dimensions (WxHxD): 77 x 158 x 16.9 mm / 3.03 x 6.22 x 0.67 in
Weight body: Ca. 308 g / 10.4 oz (inc. battery)
Color: Black

Regulatory & Safety

Product compliance: CE, CB, FCC, NCC, BSMI(TBD), IEC62133, UN38.3, UI2054, RoHS, WEEE, REACH

Items

Enclosed: Standard battery, USB adapter (QC2.0), hand strap, USB cable
Sold Separately: Extended battery, extended battery cover, protection bumper, stylus, holster, OptiCare comprehensive care for 2, 3 or 5 years
Cradle (charging and communication): USB or ethernet single charge cradle with cradle power adapter