

CRD9723RU5

Cradle for OPL9700 series

+ Models

CRD9722 Single cradle, charging

CRD9723RU Single cradle, serial communication, charging

CRD9723RU1 Multi-cradle, 1x communication, 5x charging

CRD9723RU5 Multi-cradle, 5x communication, 5x charging

CRD9726 Single cradle, Modem communication, charging

CRD9727 Single cradle, GSM communication, charging

+ Specifications

Communication

- RS232: Baudrate 2400 bps - 115.2 kbps, half duplex RS232, DB9 F connector
- RS485: Half duplex RS485, Mod 4P4 connector
- USB: Ver. 1.1, client, VCP, USB-A connector

Power

- Voltage requirement: 6 V DC
- Battery charging time: Automatically determined

Physical

- Dimensions (w x h x d): 310 x 71 x 95 mm / 12.20 x 2.80 x 3.74 in
- Weight body: Ca. 350 g / 12.3 oz
- Case: ABS, Blue

Regulatory & Safety

- Product compliance: CE, FCC, VCCI, RoHS

Enclosed items

- USB cable
- RS232 cable

Sold separately

- Power supply 6V



Copyright Opticon. All rights reserved. This information is subject to change without prior notice.

- **The Netherlands:** Hoofddorp
- **France:** ISSY Les Moulineaux CEDEX
- **Germany:** Dietzenbach
- **Italy:** Castel Maggiore (BO)
- **Spain:** Valencia
- **Sweden:** Järfälla
- **United Kingdom:** Luton, Bedfordshire
- **U.S.A.:** Orangeburg, NY - Seattle, WA
- **Japan:** Warabi City

- **Taiwan:** Taipei
- **P.R.China:** Shanghai
- **Australia:** Kariang

Opticon Sensors Europe B.V.
European headquarters
Opaallaan 35
2132 XV Hoofddorp
The Netherlands
phone: +31 (0)23-5692700
fax: +31 (0)23-5638266
email: sales@opticon.com
internet: www.opticon.com