




Description

 **NOTIFICATION DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.



Opticon CRD27 is equipped with charging and communication features for the Opticon H27 1D and H27 2D. Two slots provide charging of both the docked terminal and a spare battery.

Specifications

- Article number: 13344 Opticon CRD-27

Charging and communication cradle for:

- Opticon H-27 1D Android Smartphone Article number: 13280
- Opticon H-27 2D Android Smartphone Article number: 13281

Communication

- USB: Ver. 2.0, OTG, client and host, micro-USB connector

Power

- Voltage requirement: 5V DC, 3A
- Charging method: Battery in terminal or in spare slot

Durability

- Temperature in operation: 0 to 40 °C / 32 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F

Physical

- Dimensions (w x d x h): 74.3 x 109.2 x 97.5 mm / 2.93 x 4.3 x 3.84 in
- Weight body: 205 g / 7.23 oz
- Case: ABS/PC, Black

Regulatory & Safety

- Product compliance: CE, FCC, RoHS

Warranty

- 2 year Manufacturer warranty / Fabrieks garantie

Enclosed items

- Power supply Article number :

Sold separately

- Power cable

Features

Properties

Including: Power supply

Physical

Connection(s): USB micro