




Description

 **NOTIFICATION DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.

 1D barcode  IrDA  IP54

Model : **Opticon OPL-9725 (10993)**

Groep : *Data collector - Data collector with single key*

Datasheet: [Opticon OPL9725](#)

Opticon OPL9725 is equipped with just one key allowing easy and straight use. This model is as standard equipped with integrated barcode laser scanner, 128 kB memory, a real-time clock and supplied with a rechargeable battery.

Quick links

- Enclosed items & Accessories
- Downloads Manuals & Software

Product Features

One button operation

The Opticon OPL9725 is plain and simple use

Small size and light weight

The Opticon OPL9725 is easy to carry

Flash ROM memory

Provides program storage on the Opticon OPL9725

RAM memory

Provides data collection storage on the Opticon OPL9725

IrDA interface

Optical data transmission from Opticon OPL9725 to cradle

IP 54 Protection

Enables outdoor use for the Opticon OPL9725

Specifications

- Opticon OPL-9725 Barcode data collector with single key and IrDA interface
- Article number: 10993 Opticon OPL-9725 incl battery pack
- Former Article number: A731B0R0010

Electrical specifications

- Main battery pack: Li-Ion rechargeable 3.7 V nom. 600 mAh
- Main battery pack operating time: When making every 5 seconds 1 scan with 1 sec laserbeam on and 0.2 sec. green LED on and 0.2 sec. buzzer on, operating time is: approx. 200 hours

- Main battery condition: Different operation conditions affect the operating time
- Backup battery: Lithium rechargeable 3.5 mAh
- Backup battery operating time: > 1 week backup
- Battery management: When battery is low the data collector switches off automatically.
- Charging method: The main battery in data collector will be charged through the cradle. The backup battery will be charged by the main battery.

Optical specifications

- Light source: 650 nm visible laser diode
- Scan method: vibrating mirror
- Scan rate: 100 scans/sec
- Decode rate: 100 decodes/sec
- Reading angle: effective 44°
- Reading pitch angle: -25 to 0°, 0 to +25°
- Reading skew angle: -50 to -8°, +8 to +50°
- Reading tilt angle: -20 to 0°, 0 to +20°
- Curvature: R>15 mm (EAN8), R>20 mm (EAN13)
- Min. resolution at PCS 0.9: 0.15 mm / 6 mil
- Min. PCS value: 0.45
- Depth of field (view drawing)
- Depth of field: at PCS 0.9, UPC
- 60 - 300 mm / 2.36 - 11.81 in (res. 1.0 mm / 39 mil),
- 35 - 210 mm / 1.38 - 8.27 in (res. 0.5 mm / 20 mil),
- 35 - 120 mm / 1.38 - 4.72 in (res. 0.25 mm / 10 mil),
- 35 - 70 mm / 1.38 - 2.76 in (res. 0.15 mm / 6 mil)

Communication specifications

- Transmission speed IrDA: baudrate: 2.4 - 115.2 kbps

Identification

- Supported 1D barcode Symbologies: JAN/UPC/EAN (WPC) incl. add on, Chinese Post, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN, Korean Postal Authority code, Matrix 2of5, MSI/Plessey-UK/Plessey, RSS, S-Code, Telepen, Tri-Optic, Composite codes
- Supported 2D barcode Symbologies: MicroPDF417, PDF417 (if supported in application)

Functionality

- Trigger mode: manual
- Memory FlashROM: 512 kB (O/S and program)
- Memory RAM: 128 kB (data storage) / optional 512 kB
- Microprocessor: 16-bit
- Real time clock: Quartz RTC, time and date programmable, leap year handling, (accuracy +/- 60 sec./month)
- Keyboard: 1 scan key
- Programming: Functionality is provided by user application.

Environmental specifications

- Temperature in operation: -5 to 40 °C / 23 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F
- Humidity in operation: 20 - 80 % (non-condensing)
- Humidity in storage: 20 - 90 % (non-condensing)
- Ambient fluorescent light rejection: 3,000 lx max
- Ambient white light rejection: 3,000 lx max
- Ambient direct sun light rejection: 50,000 lx max
- Shock drop test: 1.5 m / 5 ft drop onto concrete surface
- Shock vibration test: 12 - 100 Hz with 2G for 1 hour
- Protection (dust and moisture, IEC529): IP 54

Physical specifications

- Dimensions: 125 x 44 x 19 mm / 4.92 x 1.73 x 0.75 in (view drawing)
- Case material: ABS
- Weight body: ca. 85 g / 3 oz

Regulatory

- Laser safety class: JIS-C-6802 Class 1, IEC 60825-1 Class 1, FDA CDRH Class I
- Product compliance: CE, FCC, VCCI, RoHS

Warranty

- 2 year Manufacturer warranty / Fabrieks garantie

Downloads

Enclosed items

- Rechargeable Battery pack 600 mAh **Article number : 10303**
- Handstrap for OPL-97xx **Article number : 10225**

Accessories

Sold separately.

- CRD 9722: Single charging cradle **Article number : 10998**
- CRD 9723 RU: Single serial communication cradle **Article number : 10935**
- CRD 9723 RU1: Multibay cradle, 1x communication, 5x charging **Article number : 11099**
- Nylon case for OPL-97xx and DCL15xx Fixed clip **Article number : 10839**
- Nylon case for OPL-97xx and DCL15xx Swivel clip **Article number : 10838**
- Nylon case for OPL-97xx and DCL15xx Window Swivel clip **Article number : 11211**
- CRD 9723 RU5: Multibay cradle, 5x communication, 5x charging **Article number : 11098**