




Description

NOTIFICATION **DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.



Opticon CRD9723 RU5 multibay cradle contains 5 slots to charge the battery and transmit data of Opticon's data collectors (OPL-9815, OPL-97XX and PX-36) by either the RS232 or USB interface. The cascading feature supports a network chain of this cradle by RS232 or RS485.

Specifications

• Article number: 11098 Opticon CRD9723 RU5 incl RS232 or USB cable

• Former Article number: A74070N0010

Electrical specifications

Voltage requirement: 6 V DC, +/- 10>#/li###

· Battery charging time: automatically determined

Communication specifications

• Available interfaces: RS232, USB VCP (serial port), RS485

Transmission speed: baud rate: 2.4 - 115.2 kbps

Transmission mode: half duplex RS232, half duplex RS485

Functionality

· Parity: Odd, Even, None

Physical specifications

• Dimensions: 65 x 310 x 97 mm / 2.56 x 12.20 x 3.82 in

· Case material: ABS

Weight body: Ca. 335 g / 12.2 oz

Connector RS232: DB9 F - Mod 10P10

Connector USB: USB-A - USB-B

Connector RS485: Mod 4P4 - Mod 4P4

Regulatory

Product compliance: EN 55022, EN 55024

Warranty

2 year Manufacturer warranty

Enclosed items

• Cable RS232 or USB Article number: 10299 or 10957

Accessories

Sold separately

• Power supply 6,0V / 2,0A Article number : 10991

Features

Properties

Serie(s): PX-36 OPL-97xx PX-35