




Description

 **NOTIFICATION DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.

Model : **Opticon CRD-1001 (11590)**

Groep : *Handheld terminal - Charging and communication cradle for OPH-1003, OPH-1004 and OPH-1005*

Datasheet: [Opticon CRD1001](#)

Opticon CRD1001 is equipped with charging & communication features for the OPH1003 / OPH1004 / OPH1005. Two slots provide charging of both the docked terminal and a spare battery. The external communication is supported by either RS232 or USB interface.

Specifications

- Opticon CRD-1001
- Article number : 11590 opticon CRD-1001

Electrical specifications

- Voltage requirement: 6 V DC output for terminal charging, 4.2 DC output for battery charging
- Battery charging time: max. 2 ½ hours

Communication specifications

- Available interfaces: RS232, USB VCP (serial port)
- Transmission speed: baud rate: 2.4 - 115.2 kbps
- Transmission mode: half duplex RS232

Environmental specifications

- Temperature during charging: -10 to 45 °C / 14 to 113 °F

Physical specifications

- Dimensions: 68 x 96 x 70 mm / 2.68 x 3.78 x 2.76 in
- Case material: ABS
- Weight body: ca. 110 g / 3.9 oz

Regulatory

- Product compliance: CE, FCC, VCCI, RoHS

Warranty

- 2 year Manufacturer warranty / Fabrieks garantie

Downloads

Enclosed items

- USB host client cable for CRD-1001 **Article number : 10957**
- RS232 communication cable **Article number: 12094**

Accessories

Sold separately.

- Power supply 6V **Article number : 10991**

Let op: Wordt standaard zonder powersupply geleverd.