



Description

NOTIFICATION **DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.

USB VCP-only

Model : Opticon CRD-15 (11963)

Groep : Mobile computing - Charging and communication cradle for the

H-15 series Datasheet: Opticon CRD15

Opticon CRD15 is equipped with charging & communication features for the H-15 / H-15B. Two slots provide charging of both the docked terminal and a spare battery. The external communication is supported by USB interface.

Specifications

• Article number: 11963 Opticon CRD-15

Electrical specifications

- Voltage requirement: 6 V DC
- Battery charging time: Ca. 3 hours

Communication specifications

• USB: Ver. 1.1, client, VCP (serial port), USB-A connector

Physical specifications

- Dimensions: 72 x 115 x 75 mm / 2.83 x 4.53 x 2.95 in
- Case material: ABS
- Weight body: Ca. 180 g / 6.3 oz

Regulatory

· Laser safety class: CE incl. LVD, FCC, cUL, RoHS

Warranty

• 2 year Manufacturer warranty / Fabrieks garantie

Downloads

• Download : CRD-15 installation Guide (983kb)

Enclosed items

- Power supply 6,0V/2,0A Article number : 10991
- USB host client cable for CRD-15 Article number : 11573