



Description

 **NOTIFICATION DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.

 1D barcode  Windows CE  Bluetooth  Wifi  USB  RS232  IP54

Model : **Opticon PHL-7142 (11454)**

Groep : *Rugged terminal - With 1D Long Range scan engine, Windows CE 5.0, Bluetooth, WiFi, USB, RS232, IP54*

Datasheet: [Opticon PHL7142](#)

Opticon PHL7142 ruggedized terminal is a data collection terminal combining long range barcode laser scanning with manual data entry using the alphanumeric keypad. The data from the PHL7142 can directly be send by WLAN or Bluetooth. The 3.5" LCD display on the opticon PHL7142 allows easy readability and the rubber grip enables comfortable scanning. The free CF I/O slot provides the opportunity to create an extra plug-in.

Product Features

Windows® CE 5.0 Operating System

The Opticon PHL7142 is part of the Opticon PHL7000 series consisting of ruggedized terminals, equipped with Windows CE 5.0. All terminals in this range have several wireless communication options. WLAN and Bluetooth are standard available on the Opticon PHL7000 series. Two models are also equipped with GSM and GPRS. Additional, the serial connector provides the option to use a communication cable.

physical design

The physical design of these Opticon PHL7142 terminal offers a convenient balance for user operation with a graphic LCD display and keypad with backlight, providing excellent viewing in dim or bright lighting. The series supports two different keypad variations (alphanumeric and full keypad), with non-erasable keys and three different scan engines (barcode laser scanner, long range barcode laser scanning and 2D CMOS imager). The terminals can withstand drops of 1.5 meter on concrete and are protected from water and dust up to IP 54 standards.

Power

With the 3000 mAh battery (or high capacity 4000 mAh battery) and the high performance processor, the Opticon PHL7000 series can run heavy applications. The internal SD slot can expand the data storage capacity and the accessories enable optimal use of the product.

Specifications

- Opticon PHL-7142 LR Ruggedized terminal (**Project item**)
- Article number: 11454 Opticon PHL-7142 LR 1D WLAN/BT Numeric

Operation

- CPU: Intel® PXA255 32-bits RISC 400Mhz
- O/S: Windows CE 5.0
- Software: Wordpad, Internet Explorer, Inbox, Active Sync, Messenger, Opticon scanner application, Accessories, Upgradeable via integrated SD
- RTC: Supports year, month, day, hour, minute, second (leap year supported)

Memory

- FlashROM: 64 MB
- RAM: 128 MB SDRAM
- Expansion: Integrated SD, CF Type II

Display

- Type: Graphic Transflective TFT with touch panel, 256K color with adjustable backlight
- Size: 3.5", 240 x 320 pixels
- Mode: Portrait

Operating indicators

- Visual: 2 LEDs (triple-color charging indication & dual-color scanning indication)
- Non-visual: Buzzer

Operating keys

- Entry options: 29 backlit keys total
- 16-key (alpha)numeric/control keypad
- 4-way navigation keys
- 1 function key
- 1 custom key
- control keys
- 1 power key
- 3 scan keys

Communication

- RS232: Baudrate 150 bps - 115.2 kbps, serial cable connector
- USB: Ver. 1.1, full speed, serial cable connector client, optional host
- Bluetooth: Ver. 1.2, SPP, DUN, OPP, HID (only keyboard support), output power class 2, range 5-10 m
- W-LAN: 802.11b/g, CCK, TKIP, WEP, WPA, WPA2, EAP, LEAP, PEAP, AES, PSK (pre-shared, static, dynamic), Cisco CCX compatible Ver. 4
- Audio: Speaker/microphone (mono), headset connector (stereo)
- Extension: User accessible CF Type II I/O

Power

- Rechargeable battery: Lithium-Ion, 3.7 V 3000 mAh
- High-capacity battery: Optional 3.7 V 4000 mAh
- Backup battery: 1 integrated rechargeable backup battery
- Charging method: Enclosed power supply, separate cradle IRU7000, separate car charging adapter
- Battery charging time: Ca. 4 or 5.5 hours when charging through power supply, Ca. 5 or 7 hours when charging by cradle standard battery (resp. standard or High-capacity battery)

Barcode scanner Optics

- Light source: 650 nm visible laser diode
- Scan method: Bi-directional scanning
- Scan rate: 40 scans/sec
- Reading pitch angle: -20 to 0°, 0 to +20°
- Reading skew angle: -55 to -10°, +10 to +55°
- Reading tilt angle: -5° to 0°, 0 to +5°
- Curvature: R>15 (EAN8), R>20 (EAN13)
- Min. PCS value: 0.45
- Depth of field: At PCS 0.9 Code 39
- 500 - 2800 mm / 19.69 - 110.24 in (1.4 mm / 55 mil),
- 450 - 2400 mm / 17.72 - 94.49 in (1.0 mm / 39 mil),
- 420 - 1500 mm / 16.54 - 59.06 in (0.5 mm / 20 mil),
- 600 - 980 mm / 23.62 - 38.58 in (0.33 mm / 13 mil)

Supported Symbolologies

- Supported 1D barcode Symbolologies: JAN/UPC/EAN incl. add on, Codabar/ NW-7, Code 11, Code 39, Code 93, Code 128, GS1-128 (EAN-128), GS1 DataBar (RSS), IATA, ISBN, Industrial 2of5, Interleaved 2of5, Matrix 2of5, MSI/Plessey, Telepen
- Postal code: Chinese Post, Korean Postal Authority code

Durability

- Temperature in operation: 10 to 50 °C / 14 to 122 °F
- Temperature in storage: -20 to 70 °C / -4 to 158 °F
- Humidity in operation: 5 - 95 % (non-condensing)
- Ambient light immunity: White 4,000 lx max, Fluorescent 4,000 lx max, Direct sun 80,000 lx max
- Drop test: 1.5 m / 5 ft drop onto concrete surface
- Protection rate: IP 54

Physical

- Dimensions (w x h x d): 91.3/78 x 192.5 x 60.6/42.2 mm 3.59/3.07 x 7.58 x 2.39/1.66 in
- Weight body: Ca. 600 g / 1 lb 5 oz (incl. battery)
- Case: Black

Regulatory & Safety

- Product compliance: CE, FCC, cUL, RoHS, JIS-C-6802 Class 2, IEC 60825-1 Class 2, FDA CDRH Class II

Warranty

- 2 year Manufacturer warranty / Fabrieks garantie

Downloads

Enclosed items

- USB client cable for terminal **Article number : 11463**
- Power supply for PHL-7xxx 5,0V/2,6A **Article number : 11460**
- EU Line power cord **Article number : 11461**
- Rechargeable Battery for PHL-7xxx (3.7V/3Ah) Standard **Article number : 11459**
- Standard Battery cover **Article number : 11504**
- Handstrap **Article number : 11464**
- Stylus pen **Article number : 11465**
- Earphone/Microphone set **Article number : 11462**
- Quick guide **Article number : 11466**
- CF support guide **Article number : 11467**

Accessories

Sold separately.

- RS232 serial cable for PHL-7xxx **Article number : 11475**
- USB host cable for PHL-7xxx **Article number : 11476**
- Rechargeable Battery for PHL-7xxx (3.7V/4AH) High-capacity **Article number : 11470**
- High-cap Battery cover **Article number : 11505**
- Pistol grip (comes with extra stylus pen) **Article number : 11469**
- Earphone set for PHL-7xxx / GSM **Article number : 11569**
- Holster for PHL-7xxx **Article number : 11472**
- RFID card cover **Article number : 11474** (unavailable)
- IRU-7000 Single dock cradle **Article number : 11468**
- Power supply for IRU-7000 Single dock cradle **Article number : 11477**
- USB host client cable for IRU-7000 **Article number : 11573**
- RS232 Communication cable for IRU-7000 **Article number : 90201**
- PHL-7000 Car Mount **Article number : 11695**
- Car charging adapter for PHL-7000 Car Mount **Article number : 11473**
- 4-Slots Battery Charger for PHL-7xxx incl Power supply **Article number : 11471**