



Description

 **NOTIFICATION DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.



USB

Model : **Opticon CRD-19 (11764)**

Groep : *Mobile computing - Charging and communication cradle for the H-19 series*

Datasheet: Opticon CRD19

Opticon CRD19 is equipped with charging & communication features for the Opticon H-19A and H19B series. Two slots provide charging of both the docked terminal and a spare battery. The external communication is supported by USB interface.

Specifications

- Article number: 11764 Opticon CRD-19 incl Power supply

Electrical specifications

- Voltage requirement: 5,0V DC
- Charging method: battery in terminal or in spare slot, standard battery or high capacity battery
- Battery charging time: When battery in terminal: 4 or 8 hours, Separate battery pack: 2.5 or 5 hours (resp. standard or high capacity battery)

Communication specifications

- USB: Ver. 1.1, client, USB-A connector

Environmental specifications

- Temperature during operation: 5 to 40 °C / 41 to 104 °F
- Temperature during storage: -20 to 60 °C / -4 to 140 °F

Physical specifications

- Dimensions: 76 x 89 x 90 mm / 2.99 x 3.50 x 3.54 in
- Case material: ABS
- Weight body: ca. 120 g / 4.2 oz

Regulatory

- Product compliance: CE, RoHS

Warranty

- 2 year Manufacturer warranty / Fabrieks garantie

Downloads

- Download : **CRD-19 manual** (654kb)

Enclosed items

- USB cable **Article number : 10957**
- Power supply 5,0V/3,6A **Article number : 12020EU**