




---

## Description

---

 **NOTIFICATION DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.

---

 Ethernet

Model : **Opticon CRD-19E4 (11352)**

Groep : *Mobile computing - 4 slots Charging and communication cradle for the H-19 series*

Datasheet: Opticon CRD19E4

Opticon CRD19E4 multibay cradle for the Opticon H19A and H19B contains 4 slots for battery charging and for connection to the existing customer's infrastructure by Ethernet interface. It is possible to chain 2 cradles to expand the capacity to 8 slots.

---

## Specifications

- Article number: 11352 Opticon CRD-19-E4-Multicradle incl Power supply

### Electrical specifications

- Voltage requirement: 5 V DC
- Battery charging time: automatically determined

### Communication specifications

- Available interfaces: RJ45 Ethernet (LAN, UP-Link)
- Transmission speed: 10/100 Base-T

### Environmental specifications

- Temperature in operation: -10 to 40 °C / -14 to 104 °F
- Temperature in storage: -20 to 60 °C / -4 to 140 °F

### Physical specifications

- Dimensions: 150 x 115 x 94 mm / 5.91 x 4.53 x 3.70 in
- Case material: ABS

- Weight body: ca. 670 g / 1 lb 7.6 oz

#### **Regulatory**

- Product compliance: CE, RoHS

#### **Warranty**

- 2 year Manufacturer warranty / Fabrieks garantie

#### **Downloads**

- Download : **CRD-19-E4 Quick start guide** (116kB)
- Download : **DeviceLocator, Locator application for ethernet multicradle of the H 19** (149kB)

#### **Enclosed items**

- Power supply 12V/5A **Article number : cannot be ordered separately**

#### **Accessories**

sold separately.

- Cat5e STP Patch cable 2m / 3m / 5m **Article numbers : 90401 / 90402 / 90403**