








Description

 **NOTIFICATION DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.

 1D barcode  PDF417 and MicroPDF417 (by application)  IrDA  GPS  IP54

Model : **Opticon OPL-9715 (12036)**

Groep : *Data collector - Data collector with display, keypad and GPS*

Datasheet: [Opticon OPL9715](#)

Opticon OPL9715 with integrated GPS module allows to record the geographical position with barcode data. Typically, this type of barcode data collector combines three types of registrations at once; barcode data, time stamp and position tracking.

Product Features

Real-Time Barcode Collection

The Opticon OPL9715 barcode data collector holds a high performance laser scanner for barcode scanning and has a real-time clock integrated. The scanned barcode can be stored in the on-board memory with the actual time. The barcode data collector is fast and accurate and can easily keep up with a large amount of registrations.

Designed for Mobility

The average dimensions and weight provides a convenient fit for many circumstances. The Opticon OPL9715 is elegant and light for comfortable operation, also sealed up to IP54 standards to withstand rigors of several environments. The size of the scanner has volume enough to easily detect it as a working tool, it is also sleek and can easily be carried in all kinds of mobile applications.

Clear Visibility and Convient Operation

Operation of this Opticon OPL9715 is performed by a scan button and a numeric keypad supporting alphanumeric data entry. With the results visible in the graphical LCD display the user has the convenience to scan and navigate through the loaded application and add location data.

Position Tracking by GPS

The integrated GPS module on this Opticon OPL9715 data collector adds position tracking to the data collection possibilities. The GPS receiver allows to record geographical data with the scanned barcode.

Specifications

- Opticon OPL-9715 Barcode data collector with keypad and GPS (**Project item**)
- Article number 12036 Opticon OPL-9715 Black GPS Full Keypad

Electrical specifications

- Main battery pack: Li-Ion rechargeable 3,7 V / nom. 1000 mAh
- Main battery pack operating time: Ca 50 hours (1 scan / 5 sec. excl. connection), ca. 10 hours (1 scan / 5 sec, with GPS connection). Different operation conditions affect the operating time.
- Backup battery: Rechargeable manganese silicon lithium battery 3 mAh
- Backup battery operating time: > 72 hours

- Charging method: The main battery in data collector will be charged through the cradle. The backup battery will be charged by the main battery.
- Battery charging time: Ca. 5 hours

Optical specifications

- Light source: 650 nm visible laser diode
- Scan method: vibrating mirror
- Scan rate: 100 scans/sec
- Decode rate: 100 decodes/sec
- Reading angle: effective 44°
- Reading pitch angle: -25 to 0°, 0 to +25°
- Reading skew angle: -8 to -50° / +8 to +50°
- Reading tilt angle: -20 to 0°, 0 to +20°
- Min. resolution at PCS 0.9: 0.15 mm / 6 mil
- Min. PCS value: 0.45
- Depth of field (view drawing)
- Depth of field: at PCS0.9 Code 39
- 60 - 300 mm / 2.36 - 11.81 in (res. 1.00 mm / 39 mil),
- 35 - 210 mm / 1.18 - 8.27 in (res. 0.5 mm / 20 mil),
- 35 - 120 mm / 1.18 - 4.72 in (res. 0.25 mm / 10 mil),
- 35 - 70 mm / 1.18 - 1.38 in (res. 0.15 mm / 6 mil)

Communication specifications

- Interface IrDA: Ver. 1.2, baudrate: 2.4 - 115.2 kbps
- Interface GPS: NMEA 0183, SiRF Star III, 4.8 kbps

Identification

- Supported 1D barcode Symbologies: JAN/UPC/EAN (WPC) incl. add on, Chinese Post, Codabar/NW-7, Code 11, Code 39, Code 93, Code 128, IATA, Industrial 2of5, Interleaved 2of5, ISBN-ISSN, Korean Postal Authority code, Matrix 2of5, MSI/Plessey-UK/Plessey, RSS, S-Code, Telepen, Tri-Optic, Composite codes
- Supported 2D barcode Symbologies: MicroPDF417, PDF417 (if supported in application)

Functionality

- Trigger mode: manual
- Memory FlashROM: 1 MB
- Memory RAM: 512 kB
- Microprocessor: 16-bit
- Real time clock: Quartz RTC, time and date programmable, leap year handling, (accuracy +/- 60 sec./month)
- Display: 112x64 Pixels graphic LCD with backlight
- Character fonts: min. 4 lines x 14 characters, max. 10 lines x 18 characters
- Keyboard: 18 keys total, 2 function keys, 1 scan key

Environmental specifications

- Temperature in operation: 0 to +40 °C / +23 to +104 °F
- Temperature in storage: -20 to +60 °C / -4 to +140 °F
- Humidity in operation: 20 - 85 % (non condensing)
- Humidity in storage: 20 - 90 % (non condensing)
- Ambient fluorescent light rejection: 3,000 lx max
- Ambient white light rejection: 3,000 lx max
- Ambient direct sun light rejection: 50,000 lx max
- Shock packed drop test: 1.5 m / 5 ft drop onto concrete surface
- Protection (dust and moisture, IEC529): IP 54

Physical specifications

- Dimensions: 140 x 44 x 22 mm / 5.51 x 1.73 x 0.87 in (view drawing)
- Case material: ABS
- Weight body: Ca. 115 g / 4.1 oz (incl. battery)

Regulatory

- Laser safety class: JIS-C-6802 Class 1, IEC 60825-1 Class 1, FDA CDRH Class I
- Product compliance: CE, FCC, VCCI, RoHS

Warranty

- 2 year Manufacturer warranty / Fabrieks garantie

Downloads

Enclosed items

- Rechargeable battery pack 1000 mAh **Article number : 11953**
- Handstrap for OPL-97xx **Article number : 10225**

Accessories

Sold separately.

- CRD 9722: Single charging cradle **Article number : 10998**
- CRD 9723 RU: Single serial communication cradle **Article number : 10935**
- CRD 9723 RU1: Multibay cradle, 1x communication, 5x charging **Article number : 11099**
- CRD 9723 RU5: Multibay cradle, 5x communication, 5x charging **Article number : 11098**
- Nylon case for OPL-97xx and DCL15xx Fixed clip **Article number : 10839**
- Nylon case for OPL-97xx and DCL15xx Swivel clip **Article number : 10838**
- Nylon case for OPL-97xx and DCL15xx Window Swivel clip **Article number : 11211**
- Universal Menubook **Article number : 10961**