



Description

NOTIFICATION **DISCONTINUED** | Alternatives can be found under the 'Related products' tab, or contact us for assistance.

The information below is for reference purposes only.

Ethernet

Model : **Opticon CRD-15E4 (12381)**

Groep : Mobile computing - 4 slots Charging and communication cradle

for the H-15 series

Datasheet: Opticon CRD15E4

Opticon CRD15E4 is the multi-cradle for the H15 and H15B. This cradle contains 4 slots and 4 spare battery charging bays. Connection to the existing customer's infrastructure is provided by the Ethernet interface. It is possible to chain 2 multi-cradles, to expand the capacity to 8 slots and 8 spare battery charging bays.

Specifications

Opticon CRD15E4 Multicradle for the H15

Article number: 12381 Opticon CRD15E4 Multicradle

Communication

Ethernet: RJ45 Ethernet (LAN, UP-Link), 10/100 Base-T

Power

Voltage requirement: 12V

· Battery charging time: Automatically determined

Durability

Temperature in operation: 0 to 40 °C / 32 to 104 °F

Temperature in storage: -20 to 60 °C / -4 to 140 °F

Physical

• Dimensions (w x h x d): 350 x 90 x 115 mm / 13.78 x 3.54 x 4.53 in

Weight body: Ca. 520 g / 1 lb 2.3 oz

· Case: ABS, Black

Regulatory

· Product compliance: CE, RoHS

Warranty

• 2 year Manufacturer warranty / Fabrieks garantie

Downloads

Enclosed items

wer supply 100-24	0V/1.7A, 50/60	Hz, 12V/5A
)	wer supply 100-24	wer supply 100-240V/1.7A, 50/60